



## 1982 Jeep CJ

### STANDARD EQUIPMENT

Dealer Price List  
Section 2 Page 2  
Issued: August 17, 1981  
Reissued: September 15, 1981  
#Reissued: April 1, 1982

#### INTERIOR

- Ashtray — Front
- Cigar Lighter
- Gauges — Oil; Voltmeter; Temp; Fuel
- Heater & Defroster
- Mini Carpet Mat
- Mirror — 8" Inside Rearview
- Padded Sun Visors
- Padded Instrument Panel
- Passenger Safety Rail
- Roll Bar
- Seats — Bucket Seats (*Driver & Pass.*) — Front w/Seat Belts

#### EXTERIOR

- Bumper — Front, Painted
- Lights — Head, Parking, Tail & Stop, Backup, Directional Signals, Side Safety Markers & 4-Way Hazard Flashers
- Mirror — Outside Left
- Tailgate — Movable (*CJ-7*)
- Fixed Back Panel (*CJ-5*)

#### FUNCTIONAL

- Air Cleaner — Cellulose-Fiber
- Alternator — 12 Volt, 42-Amp.
- Axle, Front — Full-Floating Hypoid; Open End; Ratio 3.54:1 (*"Dana 30"*)
- Axle, Rear — Semi-Floating Hypoid; Ratio 3.54:1
- Battery — 12 Volt (55-380 Cold Crank)
- Brakes, Service — Self-Adjusting w/Split Hydraulic System & Warning Light: Manual — Front Disc (10.4" Disc) & Rear Drum, 10" x 1.75"
- Brakes, Parking — Foot Lever Actuated w/Warning Light; Operates on Rear Wheels
- Coolant (*Engine*) — Permanent Type w/Hi-Temp Thermostat (50/50 Mixture)
- Clutch — 9.125" Diameter (10.5" Diameter — 6-cyl.)
- Engine — 151 CID, Four, 2-Barrel
- Exhaust System — Single
- Free-Wheeling Front Hubs
- Fuel Filters — Tank & In-line at Carburetor
- Fuel Tank — 15 Gal. Capacity (*Approx.*)
- Fuel Tank Skid Plate
- High Energy Ignition (Electronic Ignition System — 6-cyl.)
- Horn — Single
- Oil Filter
- Spare Tire Rear Mount (*Swing-Away*)
- Springs, Front — Longitudinal Multi-Leaf; Semi-Elliptical; Spring Rate 170 Lbs. Per Inch
- Springs, Rear — Longitudinal Multi-Leaf; Semi-Elliptical; Spring Rate 185 Lbs. Per Inch
- Steering Column — Energy-Absorbing w/Anti-Theft Ignition
- Steering Damper
- Stabilizer Bar — Front
- # ● Tires — Five; G78 x 15 (B) Black Polyglass Mud & Snow Tubeless (*Code 640*)
- Tools — Jack, Scissor Type; Combined Wheel Wrench & Jack Handle (*Under Hood*)
- Transfer Case — 2-Speed; Ratios 2.62 & 1.00 (*"Dana 300"*)
- Transmission — 4-Speed Full-Synchromesh Floor Shift
- Washers — Electric & 2-Speed Electric Wipers
- Wheels — Five; 15" x 6" L Rim; 5 Studs 5.5" Circle